

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
11 November 2004 (11.11.2004)


PCT

(10) International Publication Number
WO 2004/097451 A1

- | | |
|--|---|
| <p>(51) International Patent Classification⁷: G01S 7/292,
13/90</p> <p>(21) International Application Number:
PCT/SE2004/000654</p> <p>(22) International Filing Date: 26 April 2004 (26.04.2004)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:
0301231-7 25 April 2003 (25.04.2003) SE</p> <p>(71) Applicant (<i>for all designated States except US</i>): TELEFONAKTIEBOLAGET LM ERICSSON (publ)
[SE/SE]; S-164 83 Stockholm (SE).</p> <p>(72) Inventor; and</p> <p>(75) Inventor/Applicant (<i>for US only</i>): HELLSTEN, Hans
[SE/SE]; Mutebo Aspnäs, S-585 97 Linköping (SE).</p> | <p>(74) Agent: MOLKER, Anders; c/o Ericsson AB, Patent Unit
Radio Networks, S-431 84 Mölndal (SE).</p> <p>(81) Designated States (<i>unless otherwise indicated, for every kind of national protection available</i>): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) Designated States (<i>unless otherwise indicated, for every kind of regional protection available</i>): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LI, MC, NL, PL, PT, RO, SE, SI,</p> |
|--|---|

[Continued on next page]

- (54) Title:** RFI SUPPRESSION IN SAR



(57) Abstract: A filter scheme for broadcast interference cancellation that is computationally efficient and numerically robust Airborne Low Frequency Synthetic Aperture Radar (SAR) operating in the VHF and UHF bands has been shown. At least interference Doppler filtering or interference cancellation is utilised. The interference cancellation involves prediction of the interference for each particular reception interval of mixed interference and radar ground response. This prediction is then coherently subtracted from the incoming signal.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*